

Very efficient,

FAST & ECONOMICAL

Tillage solution.

**Rotary tiller can be operated
in wet & dry land condition**




**Gear
box**

Multi and Single speed gearbox
& Side Gear drive.



**Steel
blade**

Special design of Boron steel blades
(C and L type) used for durability



**Hitch
brackets**

Adjustable lower hitch brackets



- Hard root Zone cultivation becomes easy
- Useful to break the soil blocks.
- Useful in moisture content soil.
- Extensively used for cutting, breaking and turning of soil to bury down crop Residue



Specifications

MODEL	WORKING WIDTH	NO OF BLADES	NO OF FLANGES	WEIGHT	TRACTOR POWER
CADET MINI	1219 mm	24	6	201 kg	25 HP
CADET 36 MULTI	1560 mm	36	6	425 kg	40 - 50 HP
CADET 36 SINGLE				410 kg	
CADET 42 MULTI	1800 mm	42	7	450 kg	
CADET 42 SINGLE				430 kg	
JAWAN 36 MULTI	1560 mm	36	6	445 kg	45 - 50 HP
JAWAN 36 SINGLE				425 kg	
JAWAN 42 MULTI	1800 mm	42	7	485 kg	
JAWAN 42 SINGLE				440 kg	
CAPTAIN 36 MULTI	1560 mm	36	6	475 kg	50 HP & Above
CAPTAIN 36 SINGLE				450 kg	
CAPTAIN 42 MULTI	1800 mm	42	7	505 kg	
CAPTAIN 42 SINGLE				480 kg	
GENERAL 36 MULTI *	1560 mm	36	6	860 kg	55 HP & Above
GENERAL 42 MULTI *	1800 mm	42	7	940 kg	



Disc **ROTAVATOR**

Disc Diameter
610 mm

* Useful for banana farming & for sugarcane cultivation.

MODEL	NO. OF DISCS	WORKING WIDTH	WEIGHT	TRACTOR POWER
DISCOVERY 5D	5	5 Feet	490 kg	45 HP & Above
DISCOVERY 7D	7	6 Feet	520 kg	
DISCOVERY 9D	9	7 Feet	550 kg	

Redlands Ashlyn Motors Plc

Head Office

Karikkath Lane, MG Road,
Thrissur, Kerala - 680 001



Malumichampatti, Coimbatore,
Tamilnadu - 641 050

Factory



+ 91 487 2427392

+ 91 93491 53863

marketing@redlandsmotors.com